



EVERPURE[®]
EVP 1-2-3
SIZING GUIDE



EVERPURE® SINGLE ICE MAKERS

EV9324-21 INSURICE® SINGLE PF-I2000² SYSTEM

BUILT-IN PREFILTER REMOVES SEDIMENT AND COARSE DIRT PARTICLES



- **Cubers:** <650 lbs/day (<295 kg/day)
IMI Cornelius®, Manitowoc®, Follett®, Ice-O-Matic®
- **Flakers:** <1500 lbs/day (<680 kg/day)
IMI Cornelius, Manitowoc, Follett, Ice-O-Matic, Scotsman®

- Cartridges**
- EV9534-26 EC210 Prefilter (1 ea)
 - EV9612-22 i-2000²

Features Micro-Pure® II Media^{†**}

System available without prefilter: EV9324-01 Insurice Single

EV9324-22 INSURICE TWIN PF-I2000² SYSTEM

BUILT-IN PREFILTER REMOVES SEDIMENT AND COARSE DIRT PARTICLES



- **Cubers:** 650-1200 lbs/day (295-544 kg/day)
IMI Cornelius, Manitowoc, Follett, Ice-O-Matic, Scotsman
- **Cubers:** up to 650 lbs/day (295 kg/day)
Hoshizaki®
- **Flakers:** 1500-2500 lbs/day (680-1134 kg/day)
IMI Cornelius, Manitowoc, Follett, Ice-O-Matic, Scotsman

- Cartridges**
- EV9534-26 EC-210 Prefilter (1 ea)
 - EV9612-22 i-2000² (2 ea)

Features Micro-Pure II Media^{†**}

System available without prefilter: EV9324-02 Insurice Twin

EV9325-23 INSURICE TRIPLE PF-I4000² SYSTEM

BUILT-IN PREFILTER REMOVES SEDIMENT AND COARSE DIRT PARTICLES



- **Cubers:** 1200-1600 lbs/day (544-726 kg/day)
IMI Cornelius, Manitowoc, Follett, Ice-O-Matic, Scotsman
- **Cubers:** 650-1150 lbs/day (295-522 kg/day)
Hoshizaki, Vogt®
- **Flakers:** 2500-3500 lbs/day (1134-1588 kg/day)
IMI Cornelius, Manitowoc, Follett, Ice-O-Matic, Scotsman

- Cartridges**
- EV9534-26 EC-210 Prefilter (1 ea)
 - EV9612-32 i-4000² (3 ea)

Features Micro-Pure II Media^{†**}

System available without prefilter: EV9325-03 Insurice Triple

(Continued on next page.)

*For chloramines removal, contact Everpure Technical Service. For assistance with any ice maker not listed here, call Pentair Everpure at 800.942.1153.

**See individual system specification sheets for performance claims and FIFRA registration information.

Flake & Cube Models

High and Low Flow Rate Machines

Most problems with ice makers are water related (70% by manufacturers' estimates). Clean up the water and clean up most maintenance problems!

Chief Offenders

- **Dirt:** Wears pumps, blocks solenoids, pits evaporators
- **Chlorine*:** Gas corrodes stainless parts, surfaces rust
- **Scale Buildup:** Coats evaporator, slows harvest, lowers production, increases energy usage

Solution

Everpure Insurice Systems:

- Provide excellent flow rates for even largest machines
- Remove dirt particles down to 1/2 micron in size by mechanical means
- Reduce chlorine, prevents rusting of stainless parts
- Reduce lime scale buildup that will cause poor ice production and freeze-up

Sizing Ice Machines by Brand & Series/Capacity:

If you know the manufacturer and the "size" of the ice maker, EVP 1-2-3 will point you to the correct filter system or replacement cartridge.

These sizing recommendations are merely general guidelines. For exact sizing by equipment manufacturer and model number, visit www.everpuresizing.com or contact Pentair Everpure Technical Service: servicespecialist@pentair.com or 800.942.1153.

[†]MicroPure II – A precoat filter with AgION® antimicrobial compound that inhibits the growth of bacteria to enhance product life.

EVERPURE®

EVERPURE® SINGLE ICE MAKERS (cont'd.)

EV9325-04 INSURICE® QUAD-I4000² SYSTEM

OPTIONAL PREFILTER AVAILABLE



- **Cubers:** >1600 lbs/day (>726 kg/day)
IMI Cornelius®, Manitowoc®, Follett®, Ice-O-Matic®, Scotsman®
- **Cubers:** >1150-1500 lbs/day (>522-680 kg/day)
Hoshizaki®, Vogt®
- **Flakers:** >3500 lbs/day (>1588 kg/day)
IMI Cornelius, Manitowoc, Follett, Ice-O-Matic, Scotsman

- Cartridges**
- EV9534-26 EC-210 Prefilter (1 ea)
 - EV9612-32 i-4000² (4 ea)

Features Micro-Pure® II Media[†]***

Optional prefilter prolongs filter life in dirty water areas:
EV3114-34 Prefilter Bracket • EV9795-90 E-Series 20" (50.8 cm) Prefilter

EV9327-73 INSURICE TRIPLE 7FC-S SYSTEM

HIGH CAPACITY SCALE, CHEMICAL AND MECHANICAL CONTAMINANT REDUCTION



- **Cubers:** <1500 lbs/day (<680 kg/day)
Hoshizaki®

- Cartridges**
- EV9534-26 EC210 Prefilter (1 ea)
 - EV9692-71 7FC-S (3 ea)

MULTIPLE ICE MAKERS**

Add the total ice production of all ice machines in use and then reference the information below.

EV9327-44 INSURICE QUAD 4FC-S SYSTEM

HIGH CAPACITY SCALE, CHEMICAL AND MECHANICAL CONTAMINANT REDUCTION



- **Cubers:** <1600 lbs/day (<726 kg/day)
Hoshizaki
- **Cubers:** <2400 lbs/day (<1089 kg/day)
IMI Cornelius, Manitowoc, Follett, Ice-O-Matic, Scotsman, Crystal Tips®
- **Flakers:** <5000 lbs/day (<2268 kg/day)
IMI Cornelius, Manitowoc, Follett, Ice-O-Matic, Scotsman

- Cartridges**
- EV9534-12 EC110 Prefilter (1 ea)
 - EV9692-31 4FC-S (4 ea)

EV9327-74 INSURICE QUAD 7FC-S SYSTEM

HIGH CAPACITY SCALE, CHEMICAL AND MECHANICAL CONTAMINANT REDUCTION



- **Cubers:** >1600 lbs/day (>726 kg/day)
Hoshizaki
- **Cubers:** >2400 lbs/day (>1089 kg/day)
IMI Cornelius, Manitowoc, Follett, Ice-O-Matic, Scotsman, Crystal Tips
- **Flakers:** >5000 lbs/day (>2268 kg/day)
IMI Cornelius, Manitowoc, Follett, Ice-O-Matic, Scotsman

- Cartridges**
- EV9534-26 EC210 Prefilter (1 ea)
 - EV9692-71 7FC-S (4 ea)

These sizing recommendations are merely general guidelines. For exact sizing by equipment manufacturer and model number, visit www.everpuresizing.com or contact Pentair Everpure Technical Service: servicespecialist@pentair.com or 800.942.1153.

[†]MicroPure II – A precoat filter with AgIION® antimicrobial compound that inhibits the growth of bacteria to enhance product life.

**Total Ice Maker(s) Production. For assistance with any ice maker not listed here, call Pentair Everpure at 800.942.1153.

*** See individual system specification sheets for performance claims and FIFRA registration information.



EVERPURE® COFFEE EQUIPMENT

BREWERS 0.5 GPM (1.89 LPM) AND UNDER



- System**
- EV9275-60 QL2-OCS²
- Cartridge**
- EV9618-02 OCS²

- Brewers**
- Up to 3 lbs (1.4 kg) of coffee per day
 - Up to 17 glass pots (1/2 gal) or 13 airpots (2.5 L) brewed per day
- Capacity**
- 1,500 gallons (5,678 litres)

Features Micro-Pure® II Media^{†*}

BREWERS 0.5 GPM - 1.0 GPM (1.89 LPM - 3.78 LPM)



- System**
- EV9272-00 QL3-BH²
- Cartridge**
- EV9612-50 BH²

- Brewers**
- Up to 6 lbs (2.7 kg) of coffee per day
 - Up to 34 glass pots (1/2 gal) or 25 airpots (2.5 L) brewed per day
- Capacity**
- 3,000 gallons (11,356 litres)

Features Micro-Pure II Media^{†*}

BREWERS 1.0 GPM - 1.67 GPM (3.78 LPM - 6.32 LPM)



- System**
- QC71 Single-MH²
- Head**
- EV9272-41 QC71 Single
- Cartridge**
- EV9613-21 MH²

- Brewers**
- Up to 17 lbs (7.7 kg) of coffee per day
 - Up to 102 glass pots (1/2 gal) or 77 airpots (2.5 L) brewed per day
- Capacity**
- 9,000 gallons (34,069 litres)

Features Micro-Pure II Media^{†*}

BREWERS 1.67 GPM (6.32 LPM) AND ABOVE



- System**
- QC71 Twin-MH²
- Head**
- EV9272-22 QC71 Twin
- Cartridge**
- EV9613-21 MH² (2 ea)

- Brewers**
- Up to 34 lbs (15.4 kg) of coffee per day
 - Up to 204 glass pots (1/2 gal) or 155 airpots (2.5 L) brewed per day
- Capacity**
- 18,000 gallons (68,137 litres)

Features Micro-Pure II Media^{†*}

WATER TREATMENT FOR COFFEE & ESPRESSO



- Systems**
- EV4339-14 Claris™ XXL[†]
 - EV4339-23 Claris Head 3/8-inch QCF*
- Cartridge and head are sold separately.
- *Also available in 1/4-inch QCF and 3/8-inch BSP.
- [†]Note: If chloride or silica is present in influent water supply, consult factory prior to installing filtration.

- Brewers**
- Up to 10 lbs (4.5 kg) of coffee per day
 - Up to 60 glass pots (1/2 gal) or 45 airpots (2.5 L) brewed per day

Features Micro-Pure II Media^{†*}

Specialty coffee has been the fastest growing segment of the foodservice industry for the last several years. Various blends, flavored coffees and espresso products have “raised the bar” on coffee offerings. It’s no longer just “regular or decaf”?

But one fact remains constant – coffee is 98.7% WATER! To make good coffee or espresso you MUST start with clean, filtered, taste- and odor-free WATER!

Pentair® Everpure filters remove dirt, chlorine, off-tastes and odors, providing you with superior “ingredient quality” water.

Reverse Osmosis

Hardness and Coffee

- For hardness of 12 grains and lower you can utilize Precoat (MH, BH, etc), Claris™ or Reverse Osmosis
- For hardness above 12 grains, you should only use Reverse Osmosis

The above recommendations are based on a balance of coffee volume and water quality. An excess of either or both warrants a Reverse Osmosis solution.

These sizing recommendations are merely general guidelines. For exact sizing by equipment manufacturer and model number, visit www.everpuresizing.com or contact Pentair Everpure Technical Service: servicespecialist@pentair.com or 800.942.1153.

[†]MicroPure II – A precoat filter with AgION® antimicrobial compound that inhibits the growth of bacteria to enhance product life.

*See individual system specification sheets for performance claims and FIFRA registration information.

EVERPURE® ESPRESSO SYSTEMS

Water Treatment for Espresso



Systems

- EV9607-25 ESO⁷
- EV4339-11 Claris M
- EV4339-12 Claris L
- EV4339-13 Claris XL
- EV4339-14 Claris XXL

Heads

- EV9272-41 QC7I Single (for ESO cartridge)
- EV4339-23 Claris Head 3/8-inch QCF* (for Claris cartridges)

Cartridge and head are sold separately.

*Claris head also available in 1/4-inch QCF and 3/8-inch BSP.

†Note: If chloride or silica is present in influent water supply, consult factory prior to installing filtration.

See table below for applying the ESO and Claris to Espresso.

Everpure Claris Systems – Scale prevention and hardness can be adjusted to meet specific water recipes

Everpure ESO Systems – Scale prevention

Espresso: ESO or Claris?

	ESPRESSO		
	LOW VOLUME 150 SHOTS PER DAY	MEDIUM VOLUME 150 - 300 SHOTS PER DAY	HIGH VOLUME 301-500 SHOTS PER DAY
8 Grains Hardness	ESO ⁷ Twin	ESO ⁷ Twin	ESO ⁷ Triple
	Claris M	Claris L	Claris XL
12 Grains of Hardness	ESO ⁷ Twin	ESO ⁷ Triple	Claris XXL or RO recommended
	Claris L	Claris XL	Claris XXL

Reverse Osmosis

Hardness and Coffee

- For hardness of 12 grains and lower you can utilize Precoat (MH, BH, etc), ESO, Claris™ or Reverse Osmosis (RO)
- For hardness between 12 and 20 grains, you can utilize either a Claris or Reverse Osmosis solution
- For hardness above 20 grains, you should only use Reverse Osmosis

The above recommendations are based on a balance of coffee volume and water quality. An excess of either or both warrants a Reverse Osmosis solution.

Why would I chose Claris over ESO?

- Higher performance filtration
- Blending valve allows for customized water quality
- Five-stage (vs three-stage on the ESO) filtration





For locations that would like to use a single filtration solution for their coffee and espresso equipment, consider using the Claris family of products.

These sizing recommendations are merely general guidelines. For exact sizing by equipment manufacturer and model number, visit www.everpuresizing.com or contact Pentair Everpure Technical Service: servicespecialist@pentair.com or 800.942.1153.







FOUNTAIN DRINKS – CARBONATED ONLY

Ambient Carbonator (Carbonated Beverages Only)

1 CARBONATOR	2 CARBONATORS	3 CARBONATORS	4 CARBONATORS
			
COLDRIK® 1 EV9328-01	COLDRIK 2 EV9328-02	COLDRIK 3 EV9328-03	COLDRIK 4 EV9328-44
Cartridges • EV9534-26 (1 ea) • EV9612-56 (1 ea)	Cartridges • EV9534-26 (1 ea) • EV9612-56 (2 ea)	Cartridges • EV9534-26 (1 ea) • EV9612-56 (3 ea)	Cartridges • EV9534-12 (1 ea) • EV9692-21 (4 ea) • No scale

Cold Carbonator (Carbonated Beverages Only)

1 CARBONATOR	2 CARBONATORS	3 CARBONATORS	4 CARBONATORS
			
COLDRIK 2 EV9328-02	COLDRIK 3 EV9328-03	QC71 QUAD*-MC² HEAD: EV9336-11, CARTRIDGES: EV9612-56	COLDRIK 4 EV9328-44
Cartridges • EV9534-26 (1 ea) • EV9612-56 (2 ea)	Cartridges • EV9534-26(1 ea) • EV9612-56 (3 ea)	Cartridges • EV9612-26 (4 ea)	Cartridges • EV9534-12 (1 ea) • EV9692-21 (4 ea) • No scale

*Optional prefilter available

Inconsistent or low water pressure can cause premature filter expiration and poor quality drinks. For locations with low or inconsistent water pressure you should consider a Shurflo® Water Boost System.



You may never be called on to size a filter system for fountain drinks, but here are a few simple tips:

Question #1: Is the customer serving carbonated beverages only, or are they selling both carbonated and non-carbonated beverages?

Question #2: Is the customer using an ambient carbonator(s) or cold carbonator(s)?

Question #3: How many carbonators is the customer using?





If you know these three things, the rest is as easy as EVP 1-2-3!





Fountain beverages represent one of the highest profit items in any foodservice operation today. From convenience stores to fine dining, fountain drinks are present. A fountain drink is approximately 83% water! And that doesn't include the ice! So, for great tasting fountain drinks that customers will repeatedly order, use an Everpure filter system from Pentair® to assure quality and good taste. It's as easy as EVP 1-2-3!

These sizing recommendations are merely general guidelines. For exact sizing by equipment manufacturer and model number, visit www.everpuresizing.com or contact Pentair Everpure Technical Service: servicespecialist@pentair.com or 800.942.1153.

Water Boost Sizing	ANNUAL USAGE				NUMBER OF DISPENSERS		
	VPO SYRUP		WATER CONSUMPTION		ONE	TWO	THREE
	GALLONS	LITRES	GALLONS	LITRES			
0 - 1000	0 - 3785	0 - 5000	18,927	2-gal. (7.6-litre) Medium WB 804-023	2-gal. (7.6-litre) Medium WB 804-023	2-gal. (7.6-litre) Medium WB 804-023	
1000 - 1500	3785 - 5678	5000 - 7500	18,927 - 28,391	2-gal. (7.6-litre) Medium WB 804-023	2-gal. (7.6-litre) Medium WB 804-023	6-gal. (22.7-litre) Maxi WB 804-037	
1500 - 2000	5678 - 7571	7500 - 10,000	28,391 - 37,854	2-gal. (7.6-litre) Medium WB 804-023	2-gal. (7.6-litre) Medium WB 804-023	6-gal. (22.7-litre) Maxi WB 804-037	
2000+	7570+	10,000+	37,854+	2-gal. (7.6-litre) Medium WB 804-023	6-gal. (22.7-litre) Maxi WB 804-037	6-gal. (22.7-litre) Maxi WB 804-037	

EVERPURE® FOUNTAIN DRINKS – CARBONATED & NON-CARBONATED

Ambient Carbonator (Carbonated & Non-Carbonated Beverages)			
1 CARBONATOR	2 CARBONATORS	3 CARBONATORS	4 CARBONATORS
			
COLDRINK® 2 EV9328-02	COLDRINK 3 EV9328-03	QC71 QUAD* MC² HEAD: EV9336-11 CARTRIDGES: EV9612-56	COLDRINK 4 EV9328-74
Cartridges • EV9534-26 (1 ea) • EV9612-56 (2 ea)	Cartridges • EV9534-26 (1 ea) • EV9612-56 (3 ea)	Cartridges • EV9534-26 (4 ea)	Cartridges • EV9534-26 (1 ea) • EV9692-61 (4 ea)

Cold Carbonator (Carbonated & Non-Carbonated Beverages)			
1 CARBONATOR	2 CARBONATORS	3 CARBONATORS	4 CARBONATORS
			
COLDRINK 2 EV9328-02	COLDRINK 3 EV9328-03	COLDRINK 3-7FC EV9328-73	COLDRINK 4-7FC EV9328-74
Cartridges • EV9534-26 (1 ea) • EV9612-56 (2 ea)	Cartridges • EV9534-26 (1 ea) • EV9612-56 (3 ea)	Cartridges • EV9534-26 (1 ea) • EV9692-61 (3 ea)	Cartridges • EV9534-26 (1 ea) • EV9692-61 (4 ea)

*Optional prefilter available.

Inconsistent or low water pressure can cause premature filter expiration and poor quality drinks. For locations with low or inconsistent water pressure you should consider a Shurflo® Water Boost System.



804-023



804-037

You may never be called on to size a filter system for fountain drinks, but here are a few simple tips:

Question #1: How many carbonators are there?

Question #2: How many bag-in-box units are used monthly?

If you know these two things, the rest is as easy as EVP 1-2-3!

Fountain beverages represent one of the highest profit items in any foodservice operation today. From convenience stores to fine dining, fountain drinks are present. A fountain drink is approximately 83% water! And that doesn't include the ice! So, for great tasting fountain drinks that customers will repeatedly order, use an Everpure filter system from Pentair® to assure quality and good taste. It's as easy as EVP 1-2-3!

These sizing recommendations are merely general guidelines. For exact sizing by equipment manufacturer and model number, visit www.everpuresizing.com or contact Pentair Everpure Technical Service: servicespecialist@pentair.com or 800.942.1153.

Water Boost Sizing	ANNUAL USAGE				NUMBER OF DISPENSERS		
	VPO SYRUP		WATER CONSUMPTION		ONE	TWO	THREE
	GALLONS	LITRES	GALLONS	LITRES			
0 - 1000	0 - 3785	0 - 5000	18,927	2-gal. (7.6-litre) Medium WB 804-023	2-gal. (7.6-litre) Medium WB 804-023	2-gal. (7.6-litre) Medium WB 804-023	
1000 - 1500	3785 - 5678	5000 - 7500	18,927 - 28,391	2-gal. (7.6-litre) Medium WB 804-023	2-gal. (7.6-litre) Medium WB 804-023	6-gal. (22.7-litre) Maxi WB 804-037	
1500 - 2000	5678 - 7571	7500 - 10,000	28,391 - 37,854	2-gal. (7.6-litre) Medium WB 804-023	2-gal. (7.6-litre) Medium WB 804-023	6-gal. (22.7-litre) Maxi WB 804-037	
2000+	7570+	10,000+	37,854+	2-gal. (7.6-litre) Medium WB 804-023	6-gal. (22.7-litre) Maxi WB 804-037	6-gal. (22.7-litre) Maxi WB 804-037	



EVERPURE® STEAMERS & COMBI OVENS

Boiler Steam Ovens up to 12 Grains of Hardness

EV9797-50 KLEENSTEAM CT



- Compatible With**
- Gas boiler systems up to 125K BTU
 - Electric boiler systems up to 18 kW

- Water Requirements**
- <12.0 grains/gallon hardness
- System**
- EV9797-50 Kleensteam CT
- Cartridges**
- EV9617-16 4CB5 Carbon
 - EV9799-02 SS-10 ScaleStick®

EV9797-21 KLEENSTEAM II SINGLE



- Compatible With**
- Gas boiler systems 125 - 175K BTU
 - Electric boiler systems 18 - 48 kW

- Water Requirements**
- <12.0 grains/gallon hardness
- System**
- EV9797-21 Kleensteam II Single
- Cartridges**
- EV9618-11 7CB5 Carbon
 - EV9799-02 SS-10 ScaleStick

EV9797-22 KLEENSTEAM II TWIN



- Compatible With**
- Gas boiler systems 175K BTU & greater
 - Electric boiler systems 48 kW & greater

- Water Requirements**
- <12.0 grains/gallon hardness
- System**
- EV9797-22 Kleensteam II Twin
- Cartridges**
- EV9618-11 (2 ea) 7CB5 Carbon
 - EV9799-02 (1 ea) SS-10 ScaleStick

Direct Injection Steam up to 12 Grains of Hardness

EV4339-14 WITH A SINGLE SYSTEM



- System**
- Claris XXL[†] EV4339-14
 - Claris Head 3/8-inch QCF* EV4339-23
- Cartridge and head are sold separately.

- Compatible With**
- Rapid flash steamers 2 kW - 3 kW
 - Proofers, small flash steamers 4 kW - 10kW
 - Medium flash steam & combi 11 kW - 24 kW

- * Also available in 1/4-inch QCF and 3/8-inch BSP.
- † Note: If chloride or silica is present in influent water supply, consult factory prior to installing filtration.

Boiler & Direct Injection Steam Greater than 12 Grains of Hardness

EV9970-20 MRS-350BL WITH STORAGE TANK

FOR USE IN HARD WATER AREAS AND WITH BOILERLESS STEAMERS



- Compatible With**
- Gas boiler systems up to 175K BTU – requires 40 gallon (151.4 litre) tank
 - Gas boiler systems greater than 175K BTU – requires 80 gallon (302.8 litre) tank
 - Electric boiler systems up to 48 kW – requires 40 gallon (151.4 litre) tank
 - Electric boiler systems: 48 kW & greater – requires 80 gallon (302.8 litre) tank
 - All Boilerless Systems: For tank sizing, contact Pentair Everpure Technical Service

- Water Requirements**
- >12.0 grains/gallon hardness
- System**
- EV9970-20 MRS-350BL with appropriate sized tank; order tank separately
- Cartridges**
- EV9627-04 7TO-BW (1 ea)
 - EV9627-07 MR-350 (1 ea)
 - EV9668-24 BW-4400 (1 ea)
- Tanks**
- CH34472 40 gallon tank
 - CH34473 80 gallon tank

Steamers generally fall into two categories: electric and gas operated. Pentair® Everpure offers solutions for the smallest to the largest commercial steam equipment. Easy as EVP 1-2-3!

Steam cooking equipment is a major part of any medium to high volume foodservice operation today. Steamers are one of the most problematic pieces of kitchen equipment. They are subject to corrosion, scale buildup on controls, boiler walls, heating elements, etc. When a steamer is down, the kitchen is severely limited in production capacity and food quality. Keep 'em steaming with Everpure Kleensteam®!

These sizing recommendations are merely general guidelines. For exact sizing by equipment manufacturer and model number, visit www.everpuresizing.com or contact Pentair Everpure Technical Service: servicespecialist@pentair.com or 800.942.1153.

EVERPURE®

EVERPURE® WAREWASHING

UNDERCOUNTER AND DOOR TYPE MACHINES



System

- EV9799-11 Kleanware HTS-11 (1 ea)

Requirements & Specifications

- Mounts on hot water line to booster heater
- Up to 15 GPM (56.78 LPM) flow rate, effective to 200°F (93.3°C)
- Inhibits limescale buildup-reduces corrosion
- Simple, effective Hydroblend™ technology

Cartridges

- EV9799-22 HT-10 Cartridge (1 ea)

Usually lasts up to six (6) months depending on volume

RACK CONVEYOR AND FLIGHT LINE MACHINES



System

- EV9799-11 Kleanware HTS-11 (1 ea)

Requirements & Specifications

- Self-metering head feeds proper amount of Hydroblend to booster heater
- High temperature housing effective up to 200°F (93.3°C)
- Flow rate up to 15 GPM (56.78 LPM) for largest machines

Cartridges

- EV9799-22 HT-10 Cartridge (1 ea)

Should last four (4) to six (6) months depending on volume

EV9799-22 HT-10 REPLACEMENT CARTRIDGE



Specifications

- Scale control system featuring Hydroblend
- Inhibits mineral deposits
- Provides corrosion protection

Should last four (4) to six (6) months depending on volume

Here's the easiest spec of all... one size fits all! From the undercounter models to flight line conveyers, Kleanware® "keeps 'em washing"!

Dish machines (warewashing equipment) are an integral part of foodservice kitchen packages. From the smallest undercounter units to rack and conveyor models, warewashing equipment has to work properly for the kitchen to function.

Pentair® Everpure Kleanware systems protect the booster heaters, spray arms and interior cavities of these machines and keeps them "on line" and working properly.

These sizing recommendations are merely general guidelines. For exact sizing by equipment manufacturer and model number, visit www.everpuresizing.com or contact Pentair Everpure Technical Service: servicespecialist@pentair.com or 800.942.1153.



EVERPURE® COMBINATION SYSTEMS

EV9328-06 EVERPURE HIGH FLOW CSR TRIPLE MC² SYSTEM



System available with low pressure alarm (EV9328-05)

System

- EV9328-06 CSR Triple MC²

Requirements & Specifications

- Micro-Pure® II media effectively inhibits the growth of bacteria on the filter media that can decrease product life
- Built-in prefilter removes sediment and prolongs MC² cartridge life
- Shutoff valve, inlet and outlet pressure gauges, flushing valve
- Supports two (2) carbonators, 1200 Series ice maker, three (3) to four (4) carbonators, and high volume coffee equipment
- SR-X scale reduction feeder for ice and coffee

Cartridges

- EV9534-26 EC-210 Prefilter (1 ea)
- EV9612-56 MC² (3 ea)
- EV9799-32 SS-IMF (1 ea)

Features Micro-Pure II Media^{†*}

EV9437-10 EVERPURE HIGH FLOW CSR QUAD MC² SYSTEM



System available with low pressure alarm (EV9437-11)

System

- EV9437-10 CSR Quad MC²

Requirements & Specifications

- Micro-Pure II media effectively inhibits the growth of bacteria on the filter media that can decrease product life
- Built-in prefilter removes sediment and prolongs MC² cartridge life
- Built-in shutoff valve, inlet and outlet gauges and flushing valve
- Flow rate up to 6.7 GPM (25.4 LPM)
- Supports two (2) carbonators, 1200 Series ice maker, three (3) to four (4) carbonators, and high volume coffee equipment

Cartridges

- EV9534-26 EC-210 Prefilter (1 ea)
- EV9612-56 MC² (4 ea)
- EV9799-32 SS-IMF (1 ea)

Features Micro-Pure II Media^{†*}

EV9347-20 EVERPURE HIGH FLOW CSR PLUS XC²



System available with low pressure alarm (EV9347-21)

System

- EV9347-20 CSR Plus XC²

Requirements & Specifications

- Micro-Pure II media effectively inhibits the growth of bacteria on the filter media that can decrease product life
- High capacity, high volume system with XC² cartridges
- Surge tank provides reserve of filtered water for peak usage
- Supports two (2) carbonators, 1200 Series ice maker, three (3) to four (4) carbonators, and high volume coffee equipment
- XC² cartridges provide 40% more life than MC²s
- Up to 6.7 GPM (25.4 LPM) flow rates

Cartridges

- EV9534-26 Prefilter (1 ea)
- EV9613-10 XC² (4 ea)
- EV9799-32 SS-IMF (1 ea)

Features Micro-Pure II Media^{†*}

Great tasting soda and coffee, ice makers that stay clean and producing, FCB machines with no "off tastes", steamers that stay on line, all good reasons to use Pentair® Everpure High Flow Systems. Models support up to 7 GPM (26.5 LPM) flow rates and most feature built-in prefilters.

Everpure High Flow Combination Filter Systems are capable of serving multiple pieces of foodservice equipment from one central filtration system. Ice makers, coffee equipment, espresso, fountain beverages, drinking water and steam equipment all benefit from Pentair Everpure's pure, clean "ingredient quality" water.

From a small C-Store to a full size restaurant, great water is as easy as EVP 1-2-3!

A general rule of thumb is that each MC² or XC² cartridge has a flow rate of 1.67 GPM (6.32 LPM). Each FC cartridge has a flow rate of 2.5 GPM (9.46 LPM). Total the system flow rate demand and determine how many filters you need for your system.

# OF FILTERS	MC ² OR XC ²		FC	
	FLOW RATE		FLOW RATE	
	GPM	LPM	GPM	LPM
1	1.67	6.32	2.5	9.46
2	3.34	12.64	5	18.93
3	5.01	18.96	7.5	28.39
4	6.68	25.29	10	37.85

These sizing recommendations are merely general guidelines. For exact sizing by equipment manufacturer and model number, visit www.everpuresizing.com or contact Pentair Everpure Technical Service: servicespecialist@pentair.com or 800.942.1153.

[†]MicroPure II – A precoat filter with AgION® antimicrobial compound that inhibits the growth of bacteria to enhance product life.

(Continued on next page.)

*See individual system specification sheets for performance claims and FIFRA registration information.

EVERPURE® COMBINATION SYSTEMS (cont'd.)

EV9329-44 EVERPURE HIGH FLOW CSR QUAD 4FC SYSTEM



System

- EV9329-44 CSR Quad 4FC

Requirements & Specifications

- Extended-life 4FC cartridge features balanced chemical and mechanical reduction for optimum performance in varying water qualities
- Proprietary Fibredyne™ media effectively inhibits the growth of bacteria on the filter that can decrease product life
- Built-in prefilter removes sediment and prolongs FC cartridge life
- Built-in shutoff valve, inlet and outlet gauges and flushing valve
- Flow rate up to 10.0 GPM (37.85 LPM)
- Supports three (3) carbonators, 1201-1500 lbs (545-680 kgs) total daily ice production, and up to four (4) coffee/tea brewers and two (2) urns

Cartridges

- EV9534-12 EC110 Prefilter (1 ea)
- EV9692-21 4FC (4 ea)
- EV9799-42 SS-XL (1 ea)

EV9329-73 EVERPURE HIGH FLOW CSR TRIPLE 7FC SYSTEM



System

- EV9329-73 CSR Triple 7FC

Requirements & Specifications

- Extended-life 7FC cartridge features balanced chemical and mechanical reduction for optimum performance in varying water qualities
- Proprietary Fibredyne media effectively inhibits the growth of bacteria on the filter that can decrease product life
- Built-in prefilter removes sediment and prolongs FC cartridge life
- Built-in shutoff valve, inlet and outlet gauges and flushing valve
- Flow rate up to 7.5 GPM (28.39 LPM)
- Supports 2 carbonators, 1201-1500 lbs (545-680 kgs) total daily ice production, and up to four (4) coffee/tea brewers and two (2) urns

Cartridges

- EV9534-26 EC210 Prefilter (1 ea)
- EV9692-61 7FC (3 ea)
- EV9799-42 SS-XL (1 ea)

EV9437-32 ENDURANCE HIGH FLOW SYSTEM



System

- EV9437-32 Quad

Requirements & Specifications

- Unique pretreatment system
- SEN Cartridges with proprietary Fibredyne II media for superior contaminant reduction
- 2SR-BW Phosphate Cartridge for scale reduction
- High capacity allows for once-per-year filter change-outs
- Outstanding dirt-capturing capabilities
- Pretreatment provided by unique pleated membrane with a large surface area
- Compact design nearly the same footprint as the Everpure High Flow CSR Quad System

Cartridges

- Endurance Quad Cartridge Kit
- EV9628-72

The Endurance® High Flow System (shown below) includes an industrial pretreatment system with high capacity fine filtration that provides up to 200,000 gallons of capacity. It also includes a quick-change scale inhibition cartridge (2SRBW) in place of the SR-X and ScaleStick® found on MC² and FC High Flow CSR Systems.

These sizing recommendations are merely general guidelines. For exact sizing by equipment manufacturer and model number, visit www.everpuresizing.com or contact Pentair Everpure Technical Service: servicespecialist@pentair.com or 800.942.1153.



FILTRATION & PROCESSING SOLUTIONS

EVERPURE-SHURFLO WORLD HEADQUARTERS, 1040 MUIRFIELD DRIVE, HANOVER PARK, IL 60133 USA • WWW.EVERPURE.COM
800.942.1153 MAIN (US ONLY) • 630.307.3000 MAIN • 630.307.3030 FAX • CSEVERPURE@PENTAIR.COM EMAIL

EVERPURE-SHURFLO AUSTRALIA / NEW ZEALAND, 1-21 MONASH DRIVE, DANDENONG SOUTH, VIC 3175 AUSTRALIA
1300 576 190 TEL • AU.EVERPURE@PENTAIR.COM EMAIL

EVERPURE-SHURFLO CHINA, 21F CLOUD 9 PLAZA, NO 1118, SHANGHAI, 200052, CHINA
86.21.3211.4588 TEL • 86.21.3211.4580 FAX • CHINA.WATER@PENTAIR.COM EMAIL

EVERPURE-SHURFLO INDIA, GREEN BOULEVARD, B-9/A, 7TH FLOOR - TOWER B SECTOR 62, NOIDA - 201301
91.120.419.9444 TEL • 91.120.419.9400 FAX • INDIACUSTOMER@PENTAIR.COM EMAIL

EVERPURE-SHURFLO EUROPE, PENTAIR WATER BELGIUM BVBA, INDUSTRIEPARK WOLFSTEE, TOEKOMSTLAAN, 30 B-2200 HERENTALS, BELGIUM
+32.(0).14.283.500 TEL • +32.(0).14.283.505 FAX • SALES@EVERPURE-EUROPE.COM EMAIL

EVERPURE-SHURFLO JAPAN INC., HASHIMOTO MN BLDG. 7F, 3-25-1 HASHIMOTO, MIDORI-KU, SAGAMIHARA-SHI KANAGAWA 252-0143, JAPAN
81.(0)42.775.3011 TEL • 81.(0)42.775.3015 FAX • INFO@EVERPURE.CO.JP EMAIL

EVERPURE-SHURFLO SOUTHEAST ASIA, 390 HAVELOCK ROAD, #04-01 KING'S CENTRE, SINGAPORE 169662
65.6768 5800 TEL • 65. 6737 5149 FAX • CSEVERPURE@PENTAIR.COM EMAIL

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice.

Pentair is an equal opportunity employer.

EV7013-99 REV D FE14 © 2014 Pentair Filtration Solutions, LLC. All Rights Reserved.